



# **Technol<sup>®</sup> 400**

## **Diesel Fuel Conditioner**

### **Material Safety Data Sheet I**

#### **Section 1. General Information.**

NAME: **Technol<sup>®</sup> 400 Diesel Fuel Conditioner.**

CAS# : Mixture.

CHEM NAME: Blend of petroleum distillates.

FORMULA : Proprietary.

MOLECULAR WT : N/A.

EMERGENCY Chemtrec numbers:

USA : (800) 424-9300

INTERNATIONAL : 001-703-527-3887

Address : Technol Fuel Conditioners, Inc.  
12 Christopher Way  
Suite 102  
Eatontown NJ. 07724

Contact : Technol Fuel Conditioners, Inc.

Telephone : (800) 645-4033

ISSUE DATE: January, 1993

REVISED DATE: March, 2006

#### **Section 2. Personal Protective Equipment.**

Rubber gloves and splashproof goggles are recommended as a standard operation procedure.

#### **Section 3. Hazards Information.**

SKIN : Irritation of exposed skin due to defatting of skin.

EYES : May cause burns.

INGESTION : Irritation of gastrointestinal tract.

BIOLOGICAL : N/A.

PERMISSIBLE CONCENTRATION : Not Known.

FLAMMABLE LIMITS IN AIR (% by Vol.) : Not Established.

UNUSUAL FIRE & EXPLOSIVE HAZARDS : None Known.

INHALATION: Overexposure will cause dizziness and lack of coordination. Unlikely to occur under normal usage conditions.

UNUSUAL CHRONIC TOXICITY: Prolonged or repeated exposure to Xylene and N-Butanol causes liver, kidney, lung and CNS damage

#### **Section 4. Precautions & Procedures.**

FIRE EXTINGUISHING TO AVOID: Water.

FIRE EXTINGUISHING AGENT RECOMMENDED: Dry Chemical, CO<sub>2</sub>, Chemical Foam.

SPECIAL FIRE FIGHTING PRECAUTIONS: Firefighters should wear self-contained breathing apparatus in the positive mode with full facepiece due to likelihood of fumes, smoke and hazardous decomposition products.

SPECIAL INSTRUCTIONS: *Handle as combustible petroleum product.*

STORAGE: Keep container tightly closed during transport and storage. Store in cool dry place.

NORMAL HANDLING: Wear rubber gloves and splashproof goggles, particularly if handling large quantities.

VENTILATION: Standard room ventilation should be sufficient in large area; local exhaust recommended for confined areas and at vapor source.

SPILL OR LEAK: Ventilate area. Remove sources of ignition. Contain any spills with dikes or absorbants to prevent migration and entry into sewers or streams. Take up small spills with dry chemical absorbant. Large spills may be taken up with pump or vacuum and finished off with dry chemical absorbant. May require excavation of contaminated soil.



# **Technol<sup>®</sup> 400**

## **Diesel Fuel Conditioner**

### **Material Safety Data Sheet II**

#### **Section 5. Physical Characteristics.**

pH : N/A.  
MATERIAL IS : Liquid.  
FLASH POINT : 120°F Open Cup.  
BOILING POINT : N/A.  
VAPOR DENSITY : N/A.  
APPEARANCE & ODOR: Amber Liquid.

SPECIFIC GRAVITY : 0.86.  
SOLUBILITY IN WATER : Negligible.  
VOLATILES BY VOLUME (@20°C): 20%.  
VAPOR PRESSURE (mm Hg@20°C): 20.  
EVAPORATION RATE:  
(Butyl Acetate=1): < 1.

#### **Section 6. Reactivity Data.**

STABILITY : Product is stable.  
INCOMPATIBILITY : Strong oxidizing agents.  
CONDITIONS TO AVOID : N/A.  
HAZARDOUS DECOMPOSITION : Can form oxides of Carbon and Nitrogen.  
HAZARDOUS POLYMERIZATION : Will not occur

#### **Section 7. First Aid Measures.**

EYE CONTACT : Rinse in cool, flowing water for 15 minutes; get medical attention.  
SKIN CONTACT : Wash with soap and water, get medical attention if skin irritation persists  
INHALATION: Remove to fresh air, get medical attention. Give artificial respiration if not breathing.  
INGESTION: Get medical attention immediately - **DO NOT INDUCE VOMITING.** Give artificial respiration if breathing stops.

#### **Section 8. Environmental Concerns.**

DEGRADABILITY/AQUATIC TOXICITY : Not Known  
RCRA STATUS OF UNUSED MATERIAL : Dispose in permitted hazardous waste site.  
EPA HAZARDOUS SUBSTANCE: Yes - Reportable Quantity = 100 lbs for Ignitable substance.  
WASTE DISPOSAL METHODS: Incinerate at a registered site; disposer must comply with Federal, State and Local disposal or discharge statutes.

#### **Section 9. References**

GENERAL: Merck Index, Tenth Edition; Supplied Material Safety Data Sheets.  
PERMISSIBLE CONCENTRATION REFERENCES: ACGIH, NIOSH, OSHA; See **Registry of Toxic Effects of Chemical Substances** for specific test results and the latest regulatory standards.



**Technol Fuel Conditioners, Inc.**

Tel: 800 645-4033

www.technol.com

Fax: 732 542-0109

REV 11/06



# **Technol<sup>®</sup> 400**

## **Diesel Fuel Conditioner**

### **Material Safety Data Sheet III**

#### **Section 10. Hazardous Ingredients.**

This product is a mixture of petroleum derivatives.

This Material is NOT known to contain any Carcinogen listed under OSHA Communication Standard 29 CFR 1910 1200.

Name	: Kerosene	Glycol Ethers
Cas#	: 808-20-6	111-76-2
Appx % By Weight	: 60-80%	5-20%
Hazard	: N/A	SARA 313

Contains no "Extremely Hazardous Substances (SARA 311/312)".

---

#### **Section 11. Transportation Information.**

EMERGENCY NUMBER: (800) 424-9300 (Chemtrec). INTERNATIONAL: 001-703-527-3887

DESCRIPTION : Proprietary mixture of petroleum derivatives.

DOT HAZARD CLASS : 3. Packing group: III.

UN/NA Number:

**NA 1993**; Combustible liquid N.O.S., Contains Aromatic Naphtha and Glycol Ethers. Not regulated when shipped in a container less than 120 gallons, by ground within the US.

**UN 1993**; Flammable liquid N.O.S., Contains Aromatic Naphtha and Glycol Ethers. When shipped in a container over 120 gallons, by sea or air, or overseas.

STORE in a cool, dry place between 45°F and 85°F. Keep out of direct sunlight and away from heat sources.

Keep Container upright; do not roll; do not store in plastic - or rubber - lined containers.

---

#### **Section 12. Additional Information: Disclaimer.**

The information contained in the Material Safety Data Sheets have been derived from analysis of published data, publicly available, and supplied component Material Safety Data Sheets. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. While this information is considered accurate, Technol Fuel Conditioners, Inc. makes no warranty, expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or information and recommendations regarding this data or the results to be obtained from the use thereof. Technol Fuel Conditioners, Inc. makes no representation as to completeness or accuracy. In no event will Technol Fuel Conditioners, Inc. be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.

Distribution of the Material Safety Data is only one component of your workplace hazard communication program. It is the employer's responsibility to ensure that all employees are properly trained to recognize, evaluate and protect themselves from the risks associated with the storage, use and disposal of this and any other chemical material.