



Technol® STR-2+®

Application Chart.

For initial use double the amount shown.

Maintenance ratio is 1 gallon to every 4,000 gallons of fuel.

You Need →		=	Ounces	+	Quarts	+	Gallons	+	Pails
<i>G A L L O N S</i>	20	=	1 Ounces						
	40	=	2 Ounces						
	60	=	2.5 Ounces						
	80	=	3 Ounces						
	100	=	4 Ounces						
	125	=	4.5 Ounces						
	150	=	5 Ounces						
	175	=	6 Ounces						
	200	=	6.5 Ounces						
<i>O F F</i>	225	=	7 Ounces						
	250	=	7.5 Ounces						
	275	=	8 Ounces						
<i>F U E L</i>	300	=	9 Ounces						
	325	=	10 Ounces						
	350	=	11 Ounces						
	375	=	12 Ounces						
<i>L T O</i>	400	=	13 Ounces						
	425	=	14 Ounces						
	450	=	15 Ounces						
<i>C O N</i>	475	=	16 Ounces						
	500	=	16.5 Ounces						
	600	=	20 Ounces						
<i>D I T I O N</i>	700	=	23 Ounces						
	800	=	26 Ounces						
	900	=	29 Ounces						
<i>D I T I O N</i>	1,000	=	→		1 Quart				
	2,000	=	→		2 Quarts				
	3,000	=	→		3 Quarts				
	4,000	=	→		→		1 Gallon		
	5,000	=	→		1 Quart	+	1 Gallon		
	6,000	=	→		2 Quarts	+	1 Gallon		
	7,000	=	→		3 Quarts	+	1 Gallon		
	8,000	=	→		→		2 Gallons		
	9,000	=	→		1 Quart	+	2 Gallons		
	10,000	=	→		2 Quarts	+	2 Gallons		